
# L: Letter Lottery


Problem author: Maarten Sijm



**Problem:** In a raffle, there are $n$ codes, one is uniformly selected at random. A code consists of lowercase letters, and once the code is selected, a random letter is taken from this code. What is the lowercase letter with the highest probability? For that letter, output the probability.

# L: Letter Lottery

Problem author: Maarten Sijm




**Problem:** In a raffle, there are $n$ codes, one is uniformly selected at random. A code consists of lowercase letters, and once the code is selected, a random letter is taken from this code. What is the lowercase letter with the highest probability? For that letter, output the probability.

**Observation:** The probability that letter $j$ is chosen from code $i$ is

$$\frac{1}{n} \cdot \frac{1}{|b_i|}.$$

# L: Letter Lottery

Problem author: Maarten Sijm



**Problem:** In a raffle, there are $n$ codes, one is uniformly selected at random. A code consists of lowercase letters, and once the code is selected, a random letter is taken from this code. What is the lowercase letter with the highest probability? For that letter, output the probability.


**Observation:** The probability that letter $j$ is chosen from code $i$ is

$$\frac{1}{n} \cdot \frac{1}{|b_i|}.$$

**Solution:** Add up the probabilities for each lowercase letter, and output the maximum probability out of the letters.

# L: Letter Lottery

Problem author: Maarten Sijm



**Problem:** In a raffle, there are $n$ codes, one is uniformly selected at random. A code consists of lowercase letters, and once the code is selected, a random letter is taken from this code. What is the lowercase letter with the highest probability? For that letter, output the probability.

**Observation:** The probability that letter $j$ is chosen from code $i$ is


$$\frac{1}{n} \cdot \frac{1}{|b_i|}.$$

**Solution:** Add up the probabilities for each lowercase letter, and output the maximum probability out of the letters.

**Pitfall:** Be sure to use 64-bit floating point numbers. 32-bit floating point numbers are not precise enough.

# L: Letter Lottery

Problem author: Maarten Sijm



**Problem:** In a raffle, there are $n$ codes, one is uniformly selected at random. A code consists of lowercase letters, and once the code is selected, a random letter is taken from this code. What is the lowercase letter with the highest probability? For that letter, output the probability.

**Observation:** The probability that letter $j$ is chosen from code $i$ is

$$\frac{1}{n} \cdot \frac{1}{|b_i|}.$$


**Solution:** Add up the probabilities for each lowercase letter, and output the maximum probability out of the letters.

**Pitfall:** Be sure to use 64-bit floating point numbers. 32-bit floating point numbers are not precise enough.

**Fun fact:** Originally, jury wanted the output to be the letter with max probability. There can be very near ties, so this version needs big integer fractions.

# L: Letter Lottery

Problem author: Maarten Sijm



**Problem:** In a raffle, there are $n$ codes, one is uniformly selected at random. A code consists of lowercase letters, and once the code is selected, a random letter is taken from this code. What is the lowercase letter with the highest probability? For that letter, output the probability.

**Observation:** The probability that letter $j$ is chosen from code $i$ is

$$\frac{1}{n} \cdot \frac{1}{|b_i|}.$$

**Solution:** Add up the probabilities for each lowercase letter, and output the maximum probability out of the letters.


**Pitfall:** Be sure to use 64-bit floating point numbers. 32-bit floating point numbers are not precise enough.

**Fun fact:** Originally, jury wanted the output to be the letter with max probability. There can be very near ties, so this version needs big integer fractions.

**Running time:** $\mathcal{O}\left(\sum |b_i|\right)$.

# L: Letter Lottery

Problem author: Maarten Sijm



**Problem:** In a raffle, there are $n$ codes, one is uniformly selected at random. A code consists of lowercase letters, and once the code is selected, a random letter is taken from this code. What is the lowercase letter with the highest probability? For that letter, output the probability.

**Observation:** The probability that letter $j$ is chosen from code $i$ is

$$\frac{1}{n} \cdot \frac{1}{|b_i|}.$$

**Solution:** Add up the probabilities for each lowercase letter, and output the maximum probability out of the letters.

**Pitfall:** Be sure to use 64-bit floating point numbers. 32-bit floating point numbers are not precise enough.

**Fun fact:** Originally, jury wanted the output to be the letter with max probability. There can be very near ties, so this version needs big integer fractions.

**Running time:** $\mathcal{O}\left(\sum |b_i|\right)$.

Statistics: 66 submissions, 48 accepted, 1 unknown