


A: Animal Attire


Problem author: Leon van der Waal



- **Problem:** Pick how many items in each of the k categories such that $\prod_{i=1}^k c_i \geq n$ while minimizing the total items

A: Animal Attire


Problem author: Leon van der Waal



- **Problem:** Pick how many items in each of the k categories such that $\prod_{i=1}^k c_i \geq n$ while minimizing the total items
- **Observation:** The c_i 's shouldn't differ by more than one.

A: Animal Attire


Problem author: Leon van der Waal



- **Problem:** Pick how many items in each of the k categories such that $\prod_{i=1}^k c_i \geq n$ while minimizing the total items
- **Observation:** The c_i 's shouldn't differ by more than one.
 - Otherwise, we can increase one number and decrease another: $3 \times 3 > 2 \times 4$.

A: Animal Attire


Problem author: Leon van der Waal



- **Problem:** Pick how many items in each of the k categories such that $\prod_{i=1}^k c_i \geq n$ while minimizing the total items
- **Observation:** The c_i 's shouldn't differ by more than one.
 - Otherwise, we can increase one number and decrease another: $3 \times 3 > 2 \times 4$.
- **Naive solution:** Make all c_i 's equal.

A: Animal Attire


Problem author: Leon van der Waal



- **Problem:** Pick how many items in each of the k categories such that $\prod_{i=1}^k c_i \geq n$ while minimizing the total items
- **Observation:** The c_i 's shouldn't differ by more than one.
 - Otherwise, we can increase one number and decrease another: $3 \times 3 > 2 \times 4$.
- **Naive solution:** Make all c_i 's equal.
 - Solve for $c^k \geq n$.

A: Animal Attire


Problem author: Leon van der Waal



- **Problem:** Pick how many items in each of the k categories such that $\prod_{i=1}^k c_i \geq n$ while minimizing the total items
- **Observation:** The c_i 's shouldn't differ by more than one.
 - Otherwise, we can increase one number and decrease another: $3 \times 3 > 2 \times 4$.
- **Naive solution:** Make all c_i 's equal.
 - Solve for $c^k \geq n$.
 - This gives a solution with $k \cdot \lceil n^{1/k} \rceil$ items. We can do better.

A: Animal Attire

Problem author: Leon van der Waal




- **Problem:** Pick how many items in each of the k categories such that $\prod_{i=1}^k c_i \geq n$ while minimizing the total items
- **Observation:** The c_i 's shouldn't differ by more than one.
 - Otherwise, we can increase one number and decrease another: $3 \times 3 > 2 \times 4$.
- **Naive solution:** Make all c_i 's equal.
 - Solve for $c^k \geq n$.
 - This gives a solution with $k \cdot \lceil n^{1/k} \rceil$ items. We can do better.
- **Observation:** Not all c_i 's have to be the same.



- **Observation:** Not all c_i 's have to be the same.

A: Animal Attire


Problem author: Leon van der Waal



- **Observation:** Not all c_i 's have to be the same.
- **Solution:** Take x times $\lfloor n^{1/k} \rfloor + 1$ and $k - x$ times $\lfloor n^{1/k} \rfloor$.

A: Animal Attire

Problem author: Leon van der Waal



- **Observation:** Not all c_i 's have to be the same.
- **Solution:** Take x times $\lfloor n^{1/k} \rfloor + 1$ and $k - x$ times $\lfloor n^{1/k} \rfloor$.
- **Solution:** Loop over x to find smallest possible x for which this works.

A: Animal Attire

Problem author: Leon van der Waal



- **Observation:** Not all c_i 's have to be the same.
- **Solution:** Take x times $\lfloor n^{1/k} \rfloor + 1$ and $k - x$ times $\lfloor n^{1/k} \rfloor$.
- **Solution:** Loop over x to find smallest possible x for which this works.
- **Complexity:** Final complexity: $\mathcal{O}(k)$. Slower solutions also get AC.

A: Animal Attire


Problem author: Leon van der Waal



- **Observation:** Not all c_i 's have to be the same.
- **Solution:** Take x times $\lfloor n^{1/k} \rfloor + 1$ and $k - x$ times $\lfloor n^{1/k} \rfloor$.
- **Solution:** Loop over x to find smallest possible x for which this works.
- **Complexity:** Final complexity: $\mathcal{O}(k)$. Slower solutions also get AC.
- **Common Pitfalls:** Trying to take the logarithm on both sides but messing up logarithm rules

A: Animal Attire


Problem author: Leon van der Waal



- **Observation:** Not all c_i 's have to be the same.
- **Solution:** Take x times $\lfloor n^{1/k} \rfloor + 1$ and $k - x$ times $\lfloor n^{1/k} \rfloor$.
- **Solution:** Loop over x to find smallest possible x for which this works.
- **Complexity:** Final complexity: $\mathcal{O}(k)$. Slower solutions also get AC.
- **Common Pitfalls:** Trying to take the logarithm on both sides but messing up logarithm rules
- $x^k \geq n \nRightarrow x \geq \lfloor \log(n)/\log(k) \rfloor$

A: Animal Attire

Problem author: Leon van der Waal



- **Observation:** Not all c_i 's have to be the same.
- **Solution:** Take x times $\lfloor n^{1/k} \rfloor + 1$ and $k - x$ times $\lfloor n^{1/k} \rfloor$.
- **Solution:** Loop over x to find smallest possible x for which this works.
- **Complexity:** Final complexity: $\mathcal{O}(k)$. Slower solutions also get AC.
- **Common Pitfalls:** Trying to take the logarithm on both sides but messing up logarithm rules
- $x^k \geq n \nRightarrow x \geq \lfloor \log(n)/\log(k) \rfloor$

Statistics: 123 submissions, 15 accepted, 45 unknown